

Fabric Type BT-11/1 P

Nomenclature:

Example : BT-11/1 P

BT – basalt construction fabric

11/1 – fabric structure

P – with leno selvage

Woven fabric of high chemical (acidic and subalkali or cement) and thermal resistance are made of basalt rovings or twisted yarns with epoxy-compatible sizing. The sizing is designed to ensure the fabric compatibility with epoxy matrix and good handling and mechanical properties of the fabric. Besides standard epoxy-compatible sizing (KV-12), fabric with multi-compatible sizing (KV-11-epoxy and polyester and vinyl-ester) could be produced on request*.

Basalt fabrics could be used in different compositions for fire, sound and heat protection, in laminates production, in construction elements and equipment – as a replacement to E-glass fabrics.

Property	Unit	Normative Values	
Basalt fiber			
Density	g/cm ³	2.67	
Exploitation temperature range	°C	- 250 + 650°C	
Coefficient of linear thermal extension	1/°C	35·10 ⁻⁷	
Monofilament diameter	µm	10-13	
Moisture content	wt %	< 0,5	
Sizing content	wt %	≥ 0.4	
Specific tensile strength of the twisted yarn**	mN/tex	>650	
Fabric			
Weaving pattern		Twill 5/3	
Weight	g/sqm	400 ± 25	
Width	cm	100 ± 1	
Count	Warp	F/10cm	22 ± 1
	Weft	F/10cm	8 ± 1
Tensile strength	Warp	N	1715
	Weft	N	980
Edge		Leno selvage	
Thickness	mm	0.33± 0.03	
Quantity	rolls / pallet	16	

Basalt Woven Fabric Technical Data Sheet



Product storage and stability over time:

Basalt fabrics should be stored in the original package at the stock (indoor conditions). Rolls should be placed parallel to each other. Warranty storage period of basalt fabrics is 2 year since the date of production (in case the required conditions are ensured).

Packaging: Fabric rolls could be supplied on a wooden or plastic tube^{***} (tube diameter is 110 mm), the beginning of the fabric is fastened on a tube at the weft yarn. The length of the roll is 50 m (for 1 m width). The roll is packed into a special packaging cellular tape, with the identification label. On request the roll could be placed into a 122x30x32 cm box and fixed with a special cardboard spacers.

* - production of basalt fabric BT-11/1 on KV-11 sizing starts from volumes of 10-15 km² (please, check with us about the possibility of this product to be produced).

** - tensile testing with flat-jaw grips.

*** - please, check or specify before ordering.