

Fabric Type TBR-500

Nomenclature:

Example : TBR-500

TBR – basalt roving fabric

500 – surface density [g/sqm]

Woven fabric of high chemical (acidic and subalkali or cement) and thermal resistance are made of basalt rovings or twisted yarns with epoxy-compatible sizing. The sizing is designed to ensure the fabric compatibility with epoxy matrix and good handling and mechanical properties of the fabric. Besides standard epoxy-compatible sizing (KV-12), fabric with multi-compatible sizing (KV-11-epoxy and polyester and vinyl-ester) could be produced on request*.

Basalt fabrics could be used in different compositions for fire, sound and heat protection, in laminates production, in construction elements and equipment – as a replacement to E-glass fabrics.

Property		Unit	Normative Values
Basalt fiber			
Density		g/cm ³	2.67
Exploitation temperature range		°C	- 250 + 650°C
Coefficient of linear thermal extension		1/°C	35·10 ⁻⁷
Monofilament diameter		µm	10-13
Moisture content		wt %	< 0,5
Sizing content		wt %	≥ 0.4
Specific tensile strength of the direct/ assembled roving**		mN/tex	>700/>650
Fabric			
Weaving pattern			Plain
Weight		g/sqm	500 ± 10
Width		cm	100 ± 1
			150 ± 1
Count	Warp	F/10cm	19
	Weft	F/10cm	25
Edge			Stitched
Thickness		mm	0.45
Quantity		rolls / pallet	16

Product storage and stability over time:

Basalt fabrics should be stored in the original package at the stock (indoor conditions). Rolls should be placed parallel to each other. Warranty storage period of basalt fabrics is 2 year since the date of production (in case the required conditions are ensured).

Packaging: Fabric rolls could be supplied on a wooden or plastic tube^{***} (tube diameter is 110 mm), the beginning of the fabric is fastened on a tube at the weft yarn. The length of the roll is 80 m (for 1 m width) or 50 m (for 1.5 m width). The roll is packed into a special packaging cellular tape, with the identification label. On request the roll could be placed into a 122x30x32 cm box and fixed with a special cardboard spacers.

* - production of basalt fabric TBR-500 on KV-11 sizing starts from volumes of 2-3 km² (please, check with us about the possibility of this product to be produced).

** - tensile testing with flat-jaw grips.

*** - please, check or specify before ordering.